

Dualfix MULTI screw tie

Product description

Dualfix "MULTI" screw anchor

The dualfix Multi-tie has been developed specifically for use with:

1. timber
2. LFN PP and Nylon PA6 insulating plugs
3. KPW 8 x 50 mm multiplug

This makes the Dualfix Multi-tie the most flexible wall tie on the market, available in both Durable 4,3 mm wire, 4,0 mm stainless steel AISI 304/316/Duplex.

Technical description

- Material: Durable Coating/stainless steel AISI 304/stainless steel AISI 316/Duplex 1,4362
- Wire thickness: durable 4,3 mm; stainless steel 4,0 mm
- Tensile strength of wire: 450N-550N Durable/800N-950N stainless steel AISI 304/AISI 316/Duplex 1,4362
- Screw wire length: 70 mm
- Point of cavity wall tie: sharp point
- \bar{n} value: 50 W/mK Durable; 14 W/mK stainless steel AISI 304/316; 16 W/mK Duplex 1,4362



Durable masonry:

Code	Length (mm)	Packaging (pcs/box)
MUSCH170	170	200
MUSCH190	190	200
MUSCH210	210	200
MUSCH220	220	200
MUSCH230	230	200
MUSCH250	250	200
MUSCH275	275	200
MUSCH300	300	200
MUSCH320	320	200
MUSCH360	360	100
MUSCH400	400	100

Stainless steel, masonry:

MUSCH170RVS	170	200
MUSCH190RVS	190	200
MUSCH210RVS	210	200
MUSCH220RVS	220	200
MUSCH230RVS	230	200
MUSCH250RVS	250	200
MUSCH275RVS	275	200
MUSCH300RVS	300	200
MUSCH320RVS	320	200
MUSCH360RVS	360	100
MUSCH400RVS	400	100

Duplex steel, adhesive mortar

MUSCH170D4	170	200
MUSCH190D4	190	200
MUSCH210D4	210	200
MUSCH220D4	220	200
MUSCH230D4	230	200
MUSCH250D4	250	200
MUSCH275D4	275	200
MUSCH300D4	300	200
MUSCH320D4	320	200
MUSCH360D4	360	100
MUSCH400D4	400	100