

# KPW screw anchor

## Product description

The DualFix KPW screw anchor is developed for connecting inner walls as well as for cavity wall anchoring in combination with mineral wool and an insulation clip.

The KPW plug 8×50 mm provides excellent grip in both hollow and solid building materials.  
DualFix KPW screw anchors are available with Durable wire or stainless steel AISI 304/316 wire.

## Technical description

- Plug material KPW: Nylon PA6
- Plug length/diameter: KPW 8 × 50 mm
- Wire quality: Durable / stainless steel AISI 304 / 316
- Tensile strength wire Durable: 450 N – 550 N
- Tensile strength stainless steel AISI 304 wire: 800 N – 950 N
- Wire diameter: 4.25 mm / 4.10 mm
- Drill diameter: 8 mm
- Drill hole depth: 60 mm



## Range

Code	Description	Packaging (pcs/box)
SAKDU210	Schroefanker + universele plug durable 210 mm	200
SAKDU220	Schroefanker + universele plug durable 220 mm	200
SAKDU230	Schroefanker + universele plug durable 230 mm	200
SAKDU250	Schroefanker + universele plug durable 250 mm	200
SAKDU275	Schroefanker + universele plug durable 275 mm	200
SAKDU300	Schroefanker + universele plug durable 300 mm	200