

Product description

The WDBLS concrete screw with hex washer head features a threaded shank for the installation of permanent and temporary fixings. It is made of carbon steel and coated with a layer of electro-galvanized zinc, providing corrosion protection. The screw is intended for installing temporary fixings on construction sites, serial fixings (barriers, railings, storage racks, brackets), and the installation of light to medium steel structures.

Technical description

- Screw diameter: 6 / 8 / 10 / 12 mm
- Drill diameter: 6 / 8 / 10 / 12 mm
- Nominal anchorage depth: 55 / 65 / 75 / 95 mm
- Effective anchorage depth: 42.6 / 50.6 / 58.1 / 75.4 mm
- Drill hole depth: 65 / 75 / 85 / 105 mm
- Drive type: TX-40 / TX-45 / TX-50



Range

Code	Dimensions (mm)	Packaging (pcs/box)
WDBLS-06040	7,5 x 40 mm	100
WDBLS-06060	7,5 x 60 mm	100
WDBLS-06080	7,5 x 80 mm	100
WDBLS-08050	9,9 x 50 mm	50
WDBLS-08060	9,9 x 60 mm	50
WDBLS-08070	9,9 x 70 mm	50
WDBLS-08080	9,9 x 80 mm	50
WDBLS-10060	12,5 x 60 mm	50
WDBLS-10070	12,5 x 70 mm	50
WDBLS-10080	12,5 x 80 mm	50
WDBLS-10090	12,5 x 90 mm	50
WDBLS-10100	12,5 x 100 mm	50
WDBLS-10110	12,5 x 110 mm	50
WDBLS-10120	12,5 x 120 mm	50
WDBLS-10130	12,5 x 130 mm	50
WDBLS-10140	12,5 x 140 mm	50

Installation

